

Control cable Bedieningskabel BK



Application	: Cable with two steel wires for traction relief for the suspension of control boxes.
TECHNICAL DATA	: TYPE BK
Standards	: VDE 0250, 0281, 0293, 0472, 0473.
Remarks	: Galvanised steel wire elements on both sides, with pvc sheath.
Conductor category	: Class 6 = very flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: Yes
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -30°C to 70°C
Permitted cable outer temperature, fixed	: -40°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
-----------	-----------	-----------------------------	---------------------

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
0145612	12 x 1,5	16.5	378
0145620	20 x 1,5	21	432
0145624	24 x 1,5	21.9	445