

## Control cable Camerakabel CAM-CC



**Application** : Flexible combi cable for use in security systems, such as camera surveillance systems.

**TECHNICAL DATA** : TYPE CAM-CC

**Remarks** : 2 flexible cores + 1 x coax 75 Ohm

Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: Copolymer, thermoplastic
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
-----------	-----------	-----------------------------------	------------------------

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
0100112	2 x 0,75	11	165
0100113	3 x 0,75	11.1	167
0100114	4 x 0,75	11.6	174