

## Single core cable Jobwire ESUY UL-CSA



<b>Application</b>	: <b>Highly flexible hook-up wire with highly stranded cores. UL &amp; CSA approved. Bending radius 10 x outer diameter.</b>
<b>TECHNICAL DATA</b>	: <b>1200007</b>
Standards	: UL 1015; CSA AWM I A/B II A/B
<b>Remarks</b>	: <b>Highly flexible core construction. For example: 1.5 mm<sup>2</sup> = 385 x 0,07 mm bare copper litzes. For comparison: class 6 = 80 x 0,15 mm. Green RAL 6018/yellow RAL 1021:30%/70%.</b>
Dimension	: 6
Conductor material	: Cu, bare
Conductor category	: Class 6 = very flexible
Core insulation	: PVC
Screen	: No
Core colour	: Green/yellow
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Outer diameter approx.	: 6.5mm
Permitted cable outer temperature, in movement	: -15°C to 105°C
Permitted cable outer temperature, fixed	: -40°C to 105°C
Nominal voltage U <sub>0</sub>	: 600V
Nominal voltage U	: 600V