

Single core cable Radox GKW-LW



Application

: Especially suitable for the connection of motor windings, switchboards, white goods and lighting fixtures. Excellent high and low temperature and ozone resistance. Weatherproof, high abrasion resistance and good oil, fuel and solvents resistant.

TECHNICAL DATA

: TYPE GKW-LW

Conductor material	: Cu, tinned
Conductor category	: Class 5 = flexible
Screen	: No
Core colour	: White
Halogen free (acc. EN 60754-1/2)	: Yes
Low smoke (acc. EN 61034-2)	: Yes
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, fixed	: -40°C to 120°C

ProductNr	Dimension	Core insulation	Flame retardant	Outer diameter approx. (mm)	Nominal voltage U0 (V)	Nominal voltage U (V)
2114740	0,5	PVC	In accordance with EN 60332-1-2	1.3	600	1000
2115552	2 x 1	Polyolefin	In accordance with EN 60332-3-24	4.6	0.6	1
2115553	3 x 1	Polyolefin	In accordance with EN 60332-3-24	4.9	0.6	1
2115554	4 x 1	Polyolefin	In accordance with EN 60332-3-24	5.4	0.6	1
2114749	1	PVC	In accordance with EN 60332-1-2	1.21	600	1000
2115202	2 x 1,5	Polyolefin	In accordance with EN 60332-3-24	5.4	0.6	1
2115603	3 x 1,5	Polyolefin	In accordance with EN 60332-3-24	5.7	0.6	1
2115606	4 x 1,5	Polyolefin	In accordance with EN 60332-3-24	6.5	0.6	1
2115605	5 x 1,5	Polyolefin	In accordance with EN 60332-3-24	7.1	0.6	1
2114750	1,5	PVC	In accordance with EN 60332-1-2	2.01	600	1000
2114751	2,5	PVC	In accordance with EN 60332-1-2	2.6	600	1000