

Control cable UL LIYY-JZ



Application	: Flexible process control cable for use in apparatus and machinery. UL and CSA approved, thus suitable for export purposes.
TECHNICAL DATA	: TYPE LIYY-JZ
Standards	: UL 2587; CSA AWM I A/B II A/B
Remarks	: Outer jacket colour=RAL7001.
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Grey
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-3-24
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -5°C to 90°C
Permitted cable outer temperature, fixed	: -5°C to 90°C
Nominal voltage U	: 600V
Core protecton	: No

ProductNr	Dimension	Outer diameter approx. (mm)
1205804	4 x 4	12.5
1205805	5 x 4	14.1
1205814	4 x 6	14.2
1205824	4 x 10	17.4
1205834	4 x 16	21.9
1205844	4 x 25	25.6