

Signal-/telecommunications cable Jobsignal YY-ST 06



Application : Signal and control cable for use in intercom, telephone and security appliances.

TECHNICAL DATA : TYPE YY-ST 06

Standards : KEMA K 102-314

Remarks : Colour code according to NEN1597. Outer jacket PVCmb.

Conductor category : Class 1 = solid
 Conductor material : Cu, bare
 Stranding : Bundle
 Stranding element : Pairs
 Core insulation : PVC
 Core identification : Colour
 Screen over stranding element : None
 Screen over stranding : Foil
 Longitudinal water blocking : No
 Radial water blocking : No
 Protective sheath : No
 Armouring : No
 Material outer sheath : PVC
 Colour outer sheath : Grey
 Halogen free (acc. EN 60754-1/2) : No
 Flame retardant : In accordance with EN 60332-1-2
 Low smoke (acc. EN 61034-2) : No
 Circuit integrity : No
 Permitted cable outer temperature, fixed : -20°C to 70°C
 Outdoor use permitted : No

ProductNr	Dimension	Outer diameter approx. (mm)
-----------	-----------	-----------------------------------

ProductNr	Dimension	Outer diameter approx. (mm)
0157204	2 x 2 x 0,6	6
0157206	3 x 2 x 0,6	7.1
0157208	4 x 2 x 0,6	7.5
0157216	8 x 2 x 0,6	8.8
0157220	10 x 2 x 0,6	9.4